

# PRODUCT DATA

UN NO: none allocated

D.G CLASS: not applicable

CAS NO: none allocated

## CX 19

Concrete release agents

For spinning processes specialized

### MANUFACTURER

J.ONE CO., LTD

252 Sanjeon-ri Dunpo-myeon, Asan Si,  
Chungcheongnam-Do, Rep of KOREA

Tel: +82-41-531-7920

Fax: +82-41-531-7923

Website: [www.jonechem.com](http://www.jonechem.com)

E-mail: [dooy@jonechem.com](mailto:dooy@jonechem.com)

### DESCRIPTION

CX 19 mold release is an emulsion of natural, biodegradable water based product that will minimize surface defects and provide a quick, easy release of concrete from molds. CX 19 can be used on metal molds.

### TECHNICAL DATA

Viscosity : 50~300cps

Color: milky white

Freeze point: below -3°C

Boiling point: 100°C approx.

Vapour pressure: as for water

Flash point: not applicable

Solubility in water: fully miscible with water

PH: 8~9 approx.

VOC content: 0 g / l

Chemical reactivity: low

### APPLICATION

CX 19 is suitable for Pipes –spinning processes, hume pipes, telegraph poles etc.

(centrifugal types)

### ADVANTAGE

Economical and easy, safe to use.

- High dilution rate.
- Elimination of health risks with petrochemicals
- Ready to use from container simply add to the mixing water.
- Environmentally friendly.
- Minimization of fire risk.
- Molds can be cleaned with water.

### RECOMMENDED DOSAGE

CX 19 is very economical version of mold release agents. It shall be diluted with water before use..

### METHOD OF USE

Clean all surface prior to application of CX 19. Agitate before use. CX 19 can be applied via spraying, brushing, rolling on the molds in thin, even layers for maximum performance and economy. For a more uniform and economical application, use a sprayer equipped with a fan type nozzle.

### PRECAUTIONS

Protect from freezing  
; store at -3°C or above.  
Clean molds for no stains.

Corax CX 19

**JONE**